

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/007017 A2

(51) International Patent Classification⁷: A61F
(21) International Application Number:
PCT/NZ2004/000146
(22) International Filing Date: 9 July 2004 (09.07.2004)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
527025 16 July 2003 (16.07.2003) NZ

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and
(72) Inventor: SHAW, David, Peter [NZ/NZ]; Cossars Road, Tai Tapu, R.D. 2, Christchurch (NZ).

(74) Agent: BUCHANAN, Elspeth, Victoria; 61 Cambridge Terrace, (P.O. Box 1250), Christchurch (NZ).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PROSTHETIC VALVES FOR MEDICAL APPLICATION



(57) Abstract: A prosthetic valve in the form of a flap valve which includes one or more flaps arranged to allow movement of liquid through the valve only in one direction, in which the or each flap is made of a flexible open work structure of a medically acceptable metal such as titanium or a titanium alloy.